

Please help: My experiment with a transistor switch.....

Source: <http://sci.tech-archive.net/Archive/sci.electronics.basics/2007-01/msg00180.html>

- *From:* "royalmp2001" <royalmp2001@xxxxxxxxxx>
 - *Date:* 4 Jan 2007 16:05:54 -0800
-

I have been studying about using a transistor as a switch at:
<http://www.kpsec.freeuk.com/trancirc.htm>

I built a npn transistor switch on breadboard using a MPSA06 (HFE=100min, FT = 100MHz).

I have a 4.7K resistor connected to the base which I connect to a 0–10Mhz function generator that produces +5V square wave above 0V (positive going only).

I have a 470 Ohm resistor as the load and I connect a oscilloscope to the collector – emmitter.

The switch is powered by a 8V power supply.

I calculated the resistor values from the web site above.

I figured that as the transistor has a current gain bandwidth product of 100MHz I would have no problem with a 10MHz signal.

Well when I get upto around 4Khz, the mark to space ratio (duty cycle) starts to lessen and is no longer 1:1 (50% duty cycle).

When I get to 44Khz it is 1:2

Until finally at around 140–150Khz the spike is too narrow to see on the scope.

If this is a 100Mhz transistor why is this happening?

I want to eventually build a switch running on a 25V power supply that will track upto 10Mhz or 20Mhz using a 2SC2078 driven by the 5V square wave signal.

The load will be high resistance(>10K) with a 200 Ohm 5W power resistor in series with the output in case the output is short circuited.

.